

YORK TABLE TOP LOW SPEED CENTRIFUGE


Model No.: YSL / YSPL-152, 153, 154

Specifications:

- YSPL-152, YSPL-153, YSPL-154 Tabletop Low Speed Centrifuge is designed for the clinical research with our years of experience. Stainless rotors with variety of capacity for convenient operation.
- Microprocessor control and DC brushless motor.
- Touch panel and LCD display.
- RCF value can be calculated automatically.
- Special damping structure to reduce vibration.
- Electrical door interlock, with which centrifuge cannot work if the door is open and the door cannot be opened when it is working.
- Variety of brackets for users to convenient choice.



L 420 Rotor Options



Max.Speed: 4000rpm
Max.RCF:2200xg
Max Cap: 18x10ml
Adaptor: (7ml)



Max.Speed: 4000rpm
Max.RCF:2200xg
Max Cap: 12x20ml
Adaptor: (5ml)

Technical Parameters

Model	YSPL-152	YSPL-153	YSPL-154
Max. Speed	4200 rpm	5000 rpm	6000 rpm
Max. RCF	2760 xg	4030 xg	5120 xg
Max. Capacity	12 x 20ml	16x15ml	16 x 15ml
Speed Accuracy	±30rpm	±30rpm	±30rpm
Time Setting Range	1min to 99min	1min to 99min	1min to 99min
Noise Level	<65dB(A)	<65dB(A)	<65dB(A)
Power Supply	AC220V±22V 50/60Hz 5A	AC220V±22V 50/60Hz 5A	AC220V±22V 50/60Hz 5A
Power	250w	250w	250w
Dimension (W x D x H)	370x432x250mm	370x432x250mm	370x432x250mm
Package Dim(W x D x H)	435x580x312mm	435x580x312mm	435x580x312mm

No 2



Max.Speed: 4200rpm
Max.RCF:2760xg
Max Cap: 4x50ml



Name : Bracket
adaptor:(15ml falcon)
Rotor Cap: 4x50ml

Adaptors can be customized

No 2



Max. Speed: 4200rpm
Max. RCF: 2760xg
Max. Capacity: 12 x 15ml



Name : Bracket
Rotor Cap: 12x10ml
adaptor:(1.5ml)
(5ml), (7ml)



Name: Bracket
Rotor Capacity: 12x2x5 ml
Adaptor: (1.5ml)
(0.5ml)

No 2



Max. Speed: 4200rpm
Max. RCF: 2760xg
Max. Cap: 8 x 10ml/16x5ml



Name: Bracket
Rotor Capacity: 8x10ml



Name: Bracket
Rotor Capacity: 8x2x5ml

YSPL-152 Rotor Options

No 1



Max. Speed: 5000rpm
Max. RCF: 4030xg
Max. Cap: 24 x 10ml
Adaptor: (1.5ml)

No 2



Max. Speed: 4200rpm
Max. RCF: 2760xg



Bracket
4x50ml
Adaptor:
(15ml falcon)



Name: Bracket
4x4x15ml
Adaptor: (1.5ml)
854808 (5ml)



Name: Bracket
4x6x5ml
Adaptor: (7 ml)
(1.5ml)
(0.5ml)

YSPL-154 Rotor Options

No 1



Max. Speed: 6000rpm
Max. RCF: 5120xg
Max. Cap: 12 x 15ml

No 2



Max. Speed: 4200rpm
Max. RCF: 2760xg



Bracket
4x50ml
Adaptor:
(15ml falcon)



Name: Bracket
4x4x15ml
Adaptor: (1.5ml)
(5ml)



Name: Bracket
4x6x5ml
Adaptor: (7 ml)
(1.5ml)
(0.5ml)