

YORK HIGH SPEED HIGH CAPACITY REFRIGERATED CENTRIFUGE


Model No.: YSL / YSPL-741R

Specifications:

- YSPL-741R is an advanced technology product. It is preferred for molecular biology, cell separation and clinic medicine.
 - Microprocessor control, touch panel, LCD display, AC frequency-conversion motor, environmental compressor unit.
 - The automatic rotor identification system for avoiding over speed.
 - The protective functions of electronic door interlock, imbalance, over temperature and over speed for safe operation.
 - The electronic door interlock for safe operation.
- Store 99 kind of programs.
- Customers can choose to set speed or RCF.
 - It has high speed rotor (21000rpm) and high capacity rotor (4 x 750ml.)



Control Screen



Technical Parameters

Model	YSPL-741R
Max. Speed	21000 rpm
Max. RCF	30642 x g
Max. Capacity	4x750ml
Speed Accuracy	±30rpm
Time Setting Range	1min to 99min 59s
Temp Setting Range	-20°C to 40°C
Temp Accuracy	±2°C
Compress Assembling Unit	Non-CFC (R404aA)
Noise Level	<65dB(A)
Power Supply	AC220V±22V 50Hz 18A
Wattage	1500Kw
Dimension (W x D x H)	710x560x450mm
Package Dim(W x D x H)	1022x712x630mm

Rotor Options



No.1

Max.Speed: 21000rpm
Max.RCF: 30642xg
Rotor Capacity: 12x1.5/2.2ml
Adaptor: (0.5ml)
Adaptor: (0.2ml)



No.2

Max. Speed: 16500rpm
Max.RCF: 19175xg
Rotor Capacity: 12x5ml
Adaptor: (0.5ml)
(1.5ml)



No.3

Max.Speed: 15000rpm
Max.RCF: 23120xg
Rotor Capacity: 12x10ml
Adaptor: 805306(5ml)
805307 (1.5ml)



No.3

Max.Speed: 15000rpm
Max.RCF: 23120xg
Rotor Capacity: 6x30ml
Adaptor:(10ml)



No.4

Max.Speed: 13000rpm
Max.RCF: 17940xg
Rotor Capacity: 6x50ml
Adaptor: (30ml)
(20ml)
(15ml falcon)
(10ml)
(5ml)
(1.5ml)
(25ml)



No.4

Max.Speed: 13000rpm
Max.RCF: 17940xg
Rotor Capacity: 6x50ml falcon
Adaptor: (15ml falcon)



No.7

Max.Speed: 16500rpm
Max.RCF: 24890xg
Rotor Capacity: 24x1.5/2.2ml
Adaptor: (0.5ml), (0.2ml)



No.8

Max.Speed: 12000rpm
Max.RCF: 15805xg
Rotor Capacity: 6x85ml
Adaptor: (50ml falcon)
(15ml falcon)
(50ml)
(3x5ml)
(25ml)



No.9

Max.Speed: 10000rpm
Max.RCF: 11960xg
Rotor Capacity: 6x100ml
Adaptor: (50ml falcon)
(15ml falcon)
(50ml)
(3x5ml)
(25ml)

 No. 5 Max.Speed: 4000rpm Max.RCF:3500xg Cap: 4x750ml	 Round bucket 4 x 450ml	 4 x 500 ml falcon	 4 x 4 x 50 ml
		 4 x 300 ml	 4 x 14 x 15 ml falcon
		 4 x 500 ml	 4 x 19 x 15 ml
		 4 x 2 x 100 ml	 4 x 24 x 7 ml
		 4 x 10 x 20 ml	 4 x 37 x 7 ml
		 4 x 4 x 50 ml falcon	Adaptors can be customized

 No. 6 Max.Speed: 4000rpm Max.RCF:30400xg Cap: 4x500ml	 4x2x96well		
	 4 x 24 x 5 ml		
	 4 x 37 x 7 ml		
	 Rectangular bucket	 cap.: 4 x 250 ml	 4 x 10 x 15 ml falcon
		 4 x 4 x 50 ml falcon	 4 x 10 x 15 ml
		 4 x 4 x 50 ml	 4 x 20 x 10 ml
		 4 x 25 x 1.5 ml	 4 x 28 x 5 ml
	 Round bucket 4 x 500ml	 4 x 19 x 5 ml	 4 x 3 x 50 ml
		 4 x 9 x 15 ml	 4 x 300 ml
		 4 x 7 x 20 ml	 4 x 100 ml